

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re application of:

George Zguris et al.

Patent No. 7,160,824

Issued: January 9, 2007

Application No. 10/630,546

Filed: July 29, 2003

Confirmation No. 7494

For: GLASS COMPOSITIONS

Examiner: Gwendolyn A. Blackwell Rudasil

Art Unit: 1775

Attorney Reference No. 3533-66350-01

FILED VIA EFS

ON 12/18/08

FILED VIA ELECTRONIC FILING SYSTEM
COMMISSIONER FOR PATENTS

REQUEST FOR CERTIFICATE OF CORRECTION

The following printing errors were noted in comparing the printed patent with the papers in the attorneys' files:

In the Specification:

Column 1, lines 26 and 27, "working temperatures (about 1427°C.)." should read -
-working temperatures (temperature ranges between glass viscosity 100 and
10000 poise) of about 2600°F (about 1427°C).--.

Column 8, line 44, "(F2)" should read --(F₂)--.

Column 8, line 51, "SiO₂, Al₂O₃" should read --SiO₂, Al₂O₃--.

Column 8, line 57, "TiO₂" should read --TiO₂--.

Column 8, line 29, "TiO₂" should read --TiO₂--.

Column 14, line 11, "at plate" should read --at the plate--.

Since not all of the errors are attributable to the Patent Office, the fee of \$100.00 pursuant to 37 C.F.R. 1.20(a) is being submitted electronically herewith. The preceding corrections


remedy mistakes of a typographical nature and/or minor character. The Certificate of Correction is enclosed to make formal notice of the errors in the referenced patent.

Respectfully submitted,

KLARQUIST SPARKMAN, LLP

One World Trade Center, Suite 1600
121 S.W. Salmon Street
Portland, Oregon 97204
Telephone: (503) 595-5300
Facsimile: (503) 595-5301

By



Lisa M. Caldwell
Registration No. 41,653

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 7,160,824

DATED : January 9, 2007

INVENTOR(S) : George Zguris et al.

It is certified that an error appears or errors appear in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

In the Specification:

Column 1, lines 26 and 27, "working temperatures (about 1427°C.)." should read -- working temperatures (temperature ranges between glass viscosity 100 and 10000 poise) of about 2600°F (about 1427°C).--.

Column 8, line 44, "(F2)" should read --(F₂)--.

Column 8, line 51, "SiO₂, Al₂O₃" should read --SiO₂, Al₂O₃--.

Column 8, line 57, "TiO₂" should read --TiO₂--.

Column 8, line 29, "TiO₂" should read --TiO₂--.

Column 14, line 11, "at plate" should read --at the plate--.

MAILING ADDRESS OF SENDER:
Klarquist Sparkman, LLP
One World Trade Center, Suite 1600
121 SW Salmon Street
Portland, Oregon 97204

PATENT NO. 7,160,824
No. of add'l copies _____
(@ .30 per page)